

MATERIAL SAFETY DATA SHEET

PREMIER ANTI-SLIP DECK PAINT

Ref: 53L612

DATE: 06/04/11

REPLACES:

BY:

1. **IDENTIFICATION OF THE PREPARATION:**

PRODUCT: PREMIER ANTI-SLIP DECK PAINT **REF:** 53L642

2. **COMPOSITION/INFORMATION ON INGREDIENTS:**

INGREDIENTS: Aliphatic Hydrocarbons R10, 52, 53 25 – 35%

3. **HAZARDS IDENTIFICATION:**

Harmful by inhalation and in contact with skin, irritating to eyes and respiratory system, flammable.

4. **FIRST AID MEASURES:**

INHALATION: Remove to fresh air, if conscious turn into recovery position. Get medical help.

SKIN: Wash with soap and water.

EYES: Flush out with clean water for 10 minutes. Get medical help.

INGESTION: Seek urgent medical attention.

5. **FIRE FIGHTING MEASURES:**

SMALL FIRES: Use Carbon Dioxide, dry chemical, foam, sand, earth or water fog.

LARGE FIRES: Use foam or water fog. Keep containers cool by spraying with water.

N.B.

Decomposition products will give rise to toxic fumes.

Self-contained breathing apparatus must be worn.

6. **ACCIDENTAL RELEASE MEASURES:**

In case of spillage, extinguish all ignition sources; avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage using vermiculite, dry sand and place in container. Avoid inhaling vapour, evacuate personnel from the area. If it has entered the drains, inform the appropriate authorities (fire service).

7. **HANDLING & STORAGE:**

Avoid contact with skin or eyes. Avoid breathing vapour. Handle in a well-ventilated workspace.

Empty containers may contain explosive vapours. Flush empty containers with water to remove residual flammable liquid and vapours. Smoking in area is prohibited. Remove all equipment, which may be sources of ignition, from vicinity while handling.

8. **EXPOSURE CONTROL/PERSONAL PROTECTION:**

INGREDIENT CAS no **STD LONGTERM EXPOSURE (8HRSH)** **ORT TERM EXPOSURE**

Aliphatic

Hydrocarbons 64742-82-1 OEL 100 ppm 125 ppm

EYE PROTECTION:

Close fitting goggles or face shield

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942

Tel: 01884 220016



MATERIAL SAFETY DATA SHEET

PREMIER ANTI-SLIP DECK PAINT

Ref: 53L612

SKIN PROTECTION: Overalls with solvent resistant gloves

RESPIRATORY PROTECTION: In poorly ventilated areas a cartridge mask suitable for solvent vapours and toxic particles is recommended.

9. PHYSICAL & CHEMICAL PROPERTIES

COLOUR:	Various
GLOSS:	Full
VISCOSITY:	6 – 8 poise R/T @ 20°C
DRYING:	Touch Dry: 4 – 6 hrs Hard Dry: O/N
CURE:	N/A
APPLICATION VISC:	As supplied
THINNERS:	50/2
MIXING RATIO:	N/A
SUPPLIED SOLIDS:	45 +/- 5%by weight 37 +/- 5%by Volume
CALCULATED SUPPLIED V.O.C:	500gms/Ltr
COVERAGE:	13 – 15sqm/Ltr @25microns DFT
FLASH POINT:	22 – 55°C
RESISTANCE:	N/A
S.G:	1.09 +/- 0.03

10. STABILITY & REACTIVITY:

STABILITY:	Stable
REACTION WITHWATER:	None
DANGEROUS REACTIONS:	None known
HAZARDOUS POLYMERISATION:	Will not occur
MATERIALS TO AVOID:	Strong oxidising agents
DANGEROUS DECOMPOSITION PRODUCTS:	CarbonMonoxide, Carbon dioxide and Nitrogen Dioxide. Nitrogen Dioxide reacts with water to form corrosive Nitric Acid.

11. TOXICOLOGICAL INFORMATION:

Can cause irritation to eyes, mucous membranes and skin.

12. ECOLOGICAL INFORMATION:

Harmful to the aquatic environment, may cause long-term adverse effects to the aquatic environment.

13. DISPOSAL CONSIDERATIONS:

This material must be disposed of via an Authorised Waste Disposal Company in accordance with Local and National Waste Disposal Regulations.

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Tel: 01884 220016
Email: Sales@premiermarinepaints.com
www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942



MATERIAL SAFETY DATA SHEET

PREMIER ANTI-SLIP DECK PAINT

Ref: 53L612

14. TRANSPORT INFORMATION:

HAZARD CLASS: 3
UN NUMBER: 1263
HAZARD LABEL: Flammable Liquid Paint Class 3
PACKING GROUP: 3
TREMCARD NO: 33
MARINE POLLUTANT: Yes
A.D.R.: Class 3 item 3,1 (c)

15. REGULATORY INFORMATION:

PRIMARY RISK: Flammable
SECONDARY RISK: Harmful
LABEL RISK PHRASES: **R10** Flammable
R20 Harmful by inhalation
R21 Harmful by contact with skin
R22 Harmful if swallowed
R23 Toxic by inhalation
R38 Irritating to skin
R52 Harmful to aquatic environment
R53 May cause long-term adverse effects in the aquatic environment

LABEL SAFETY PHRASES: **S9** Keep containers in a well-ventilated place
S16 Keep away from sources of ignition
S23 Do not breathe vapour
S29 Do not empty into drains
S33 Take precautionary measures against static discharge
S38 In case of insufficient ventilation wear suitable respiratory

16. OTHER INFORMATION:

For further Health and Safety information contact the above address.

The information given in this leaflet has been compiled on the basis of best availability knowledge. It does not imply that the information is complete or accurate in all cases. It is the user's responsibility to satisfy him/herself as to the implication of the information and/or the recommendations given for his/her own use.

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942

Tel: 01884 220016

