

MATERIAL SAFETY DATA SHEET

PREMIER HULL & TOPSIDE UNDERCOAT

Ref: 52L643

DATE: 06/04/11

REPLACES:

BY:

1. IDENTIFICATION OF THE PREPARATION:

PRODUCT: PREMIER HULL & TOPSIDE UNDERCOAT

REF: 52L643

2. COMPOSITION/INFORMATION ON INGREDIENTS:

INGREDIENTS: Aliphatic Hydrocarbons R10, 52, 53 Xn 28 – 33%

3. HAZARDS IDENTIFICATION:

Harmful by inhalation and in contact with skin, irritating to eyes and respiratory system, flammable.

4. FIRST AID MEASURES:

INHALATION: Remove to fresh air, if conscious turn into recovery position. Get medical help.

SKIN: Wash with soap and water.

EYES: Flush out with clean water for 10 minutes. Get medical help.

INGESTION: Seek urgent medical attention.

5. FIRE FIGHTING MEASURES:

SMALL FIRES: Use Carbon Dioxide, dry chemical, foam, sand, earth or water fog.

LARGE FIRES: Use foam or water fog. Keep containers cool by spraying with water.

N.B.

Decomposition products will give rise to toxic fumes.

Self-contained breathing apparatus must be worn.

6. ACCIDENTAL RELEASE MEASURES:

In case of spillage, extinguish all ignition sources; avoid sparks, flames, heat and smoking.

Ventilate. Absorb spillage using vermiculite, dry sand or earth and place in container. Avoid inhaling vapour, evacuate personnel from the area. If it has entered the drains, inform the appropriate authorities (fire service).

7. HANDLING & STORAGE:

Avoid contact with skin or eyes. Avoid breathing vapours. Handle in a well-ventilated workspace.

Empty containers may contain explosive vapours. Flush empty containers with water to remove residual flammable liquid and vapours. Smoking in area is prohibited. Remove all equipment, which may be sources of ignition, from vicinity while handling.

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942

Tel: 01884 220016



MATERIAL SAFETY DATA SHEET

PREMIER HULL & TOPSIDE UNDERCOAT

Ref: 52L643

8. EXPOSURE CONTROL/PERSONAL PROTECTION:

INGREDIENT	CAS no	STD	LONGTERM EXPOSURE (8HF)	SHORT TERM EXPOSURE
Aliphatic Hydrocarbons	64742-82-1	OEL	100 ppm	125 ppm

EYE PROTECTION:	Close fitting goggles or face shield
SKIN PROTECTION:	Overalls with solvent resistant gloves
RESPIRATORY PROTECTION:	In poorly ventilated areas a cartridge mask suitable for solvent vapours and toxic particles is recommended.

9. PHYSICAL & CHEMICAL PROPERTIES

COLOUR:	Various
GLOSS:	Matt
VISCOSITY:	10 – 12 poise R/T @ 20°C
DRYING:	Touch Dry: 2-4 hrs Hard Dry: O/N
CURE:	N/A
APPLICATION VISC:	As supplied
THINNERS:	50/2
MIXING RATIO:	N/A
SUPPLIED SOLIDS:	70 +/-5% by weight 50+/- 3% by Volume
CALCULATED SUPPLIED V.O.C:	400 +/- 20gms/Ltr
COVERAGE:	18 – 20sqm/Ltr @ 25microns
FLASH POINT:	22– 55°C
RESISTANCE:	N/A
S.G:	1.33 +/- 0.03

10. STABILITY & REACTIVITY:

STABILITY:	Stable
REACTION WITH WATER:	None
DANGEROUS REACTIONS:	None known
HAZARDOUS POLYMERISATION:	Will not occur
MATERIALS TO AVOID:	Strong oxidising agents

DANGEROUS DECOMPOSITION PRODUCTS:

Carbon Monoxide, Carbon dioxide and Nitrogen Dioxide. Nitrogen Dioxide reacts with water to form corrosive Nitric Acid.

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942

Tel: 01884 220016



MATERIAL SAFETY DATA SHEET

PREMIER HULL & TOPSIDE UNDERCOAT

Ref: 52L643

11. **TOXICOLOGICAL INFORMATION:**

Can cause irritation to eyes, mucous membranes and skin.

12. **ECOLOGICAL INFORMATION:**

Harmful to the aquatic environment, may cause long-term adverse effects to the aquatic environment.

13. **DISPOSAL CONSIDERATIONS:**

This material must be disposed of via an Authorised Waste Disposal Company in accordance with Local and National Waste Disposal Regulations.

14. **TRANSPORT INFORMATION:**

HAZARD CLASS:	3
UN NUMBER:	1263
HAZARD LABEL:	Flammable Liquid Paint Class 3
PACKING GROUP:	3
TREMCARD NO:	33
MARINE POLLUTANT:	Yes
A.D.R:	
Class 3 item 3,1 (c)	

15. **REGULATORY INFORMATION:**

PRIMARY RISK:	Flammable
SECONDRY RISK:	Harmful
LABEL RISK PHRASES:	R10 Flammable

R20 Harmful by inhalation

R21 Harmful by contact with skin

R22 Harmful if swallowed

R23 Toxic by inhalation

R38 Irritating to skin

R52 Harmful to aquatic environment

R53 May cause long-term adverse effects in the aquatic environment

Tel: 01884 220016

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942



MATERIAL SAFETY DATA SHEET

PREMIER HULL & TOPSIDE UNDERCOAT

Ref: 52L643

LABEL SAFETY PHRASES:

- S9** Keep containers in a well-ventilated place
- S16** Keep away from sources of ignition
- S23** Do not breathe vapour
- S29** Do not empty into drains
- S33** Take precautionary measures against static discharge
- S38** In case of insufficient ventilation wear suitable respiratory equipment

16. OTHER INFORMATION:

For further Health and Safety information contact the above address.

The information given in this leaflet has been compiled on the basis of best availability knowledge. It does not imply that the information is complete or accurate in all cases. It is the user's responsibility to satisfy him/herself as to the implication of the information and/or the recommendations given for his/her own use.

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942

Tel: 01884 220016

