

TECHNICAL DATA SHEET

MULTI-PURPOSE METALLIC PRIMER

Universal primer suitable for above and below the waterline on all substrates with good waterproofing and corrosion resisting performance. Also suitable as a primer or barrier coat under PREMIER and other traditional antifoulings. Contains leafing pigment (excellent sealing/binding properties). Easy to apply and relatively quick drying.



Surface Preparation

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and salt. Please refer to the Material Safety Data Sheet for further information.

*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The

Application

Application method: Brush Conventional spray Airless spray Roller
Thinner: PREMIER Antifouling Thinners
Cleaning of tools: PREMIER Antifouling Thinners

Area of use:	Boat hulls, topsides and superstructure.
Substrates:	GRP, wood, steel and ferro cement.
Packing:	1 litre and 2.5 litre
Colour:	Grey
Finish:	Matt
Volume solids:	60%
Theoretical spreading rate:	12sq.metres per litre
Flash point:	42°C
Specific gravity:	1.17
Dry to touch:	2 hours
Overcoating time:	6 hours

HEALTH & SAFETY

Refer to M.S.D.S. prior to use
Provide adequate ventilation
Prolonged skin contact
Inhalation of vapour must be avoided
Eye contamination - Flush with eyewash or warm water for 10 minutes
Clean hands after use

Any person or company using this product without first making enquiries as to the suitability for the intended purpose does so at their own risk, and Premier Marine Paints Ltd can accept no liability for

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942

