

# TECHNICAL DATA SHEET

## PREMIER ANTI-SLIP DECK PAINT

REF: 53L612

An extremely tough and hard wearing anti slip deck paint. Contains a fine mineral aggregate providing a slip resistant surface. Easy to apply and quick drying. Low sheen finish.



### Surface Preparation

Ensure surface is free from rust, moisture, oil or other surface contamination.

#### *Previous Painted Surfaces*

On previous painted surfaces if in good condition wash down with detergent, rinse with fresh water and allow to dry, then key/abrade with a fine 280-320 grade (grit) Paper. If the previously painted surface is in poor condition then we recommend removing all the previous coatings and the prime Using Premier Hull & topside undercoat. For details on surface preparation and application of Premier Hull & Topside undercoat please refer to separate data sheet for this product.

#### *GRP*

Degrease with solvent or suitable cleaner. Key /abrade well using a 60 – 120 grade paper. The clean well and allow to dry before application. If the GRP gel coat is in poor condition and weathered then due to the surface being potentially porous apply Premier Hull and topside primer to seal the gel coat before application. Again for details on surface preparation and application of Premier Hull & Topside undercoat please refer to separate data sheet for this product.

#### *Aluminium*

Degrease with solvent or suitable cleaner. Key /abrade well using a 24 – 120 grade paper. The clean well and allow to dry before application. Prime with Premier Hull & topside undercoat.

#### *Bare Wood*

Sand smooth with 80 – 180 grade/grit paper then a 280 grade/grit paper. After sanding ensure dust is removed by dusting a wiping.

|                            |                          |
|----------------------------|--------------------------|
| PACKAGE SIZE               | 1 Litre                  |
| COLOUR                     | BS 4800, BS 381C, R.A.L. |
| FLASH POINT                | Above 32°C               |
| DRYING TIME @ 20°C         | Surface Dry: 4-6 hours   |
| VOLUME SOLIDS              | 35% (+/- 2%)             |
| RECOMMENDED W.F.T.         | 75 microns               |
| RECOMMENDED D.F.T.         | 30 microns               |
| THEORETICAL SPREADING RATE | 12 Sq. Metres/Litre      |
| THINNERS                   | No. 2                    |
| SHELF LIFE                 | 12 months                |
| V.O.C.                     | 471 g/litre              |

### Application

May be applied by brush or roller. Do not apply too thickly as this may impair through drying.

Do not apply in temperatures below 5°C and ensure that the substrate temperature is above 5°C

### HEALTH & SAFETY

Refer to M.S.D.S. prior to use  
Provide adequate ventilation  
Prolonged skin contact  
Inhalation of vapour must be avoided  
Eye contamination - Flush with eyewash or warm water for 10 minutes  
Clean hands after use

Any person or company using this product without first making enquiries as to the suitability for the intended purpose does so at their own risk, and Premier Marine Paints Ltd can accept no liability for

Premier Marine Paints Ltd  
The Engine Shed  
Lenham Heath Road  
Lenham Heath  
Maidstone  
Kent  
ME17 2BS

Tel: 01884 220016  
Email: [Sales@premiermarinepaints.com](mailto:Sales@premiermarinepaints.com)

[www.premiermarinepaints.com](http://www.premiermarinepaints.com)

VAT No: 139600418  
Company Registration No: 8002942

