

TECHNICAL DATA SHEET

PREMIER BILGE/LOCKER PAINT REF: - 70L677

A water based bilge paint, ideal for all bilge areas, giving good resistance to oil, grease, salt water and fresh water.



PACKAGE SIZE	1 & 3 Litre.
COLOUR	Various
FLASH POINT	Above 55°C
DRYING TIME	Surface Dry: 2-3 hours
VOLUME SOLIDS	50% (+/- 3%)
RECOMMENDED W.F.T.	110 microns
RECOMMENDED D.F.T.	50 microns
THEORETICAL SPREADING RATE	11 Sq. Metres/Litre
THINNERS	Water
SHELF LIFE	12 months (Protected from frost)

SURFACE PREPERATION

Ensure surface is free from rust, moisture, oil or other surface contamination.

APPLICATION

May be applied by brush or roller. Do not apply too thickly as this may impair through drying.

HEALTH & SAFETY

Refer to M.S.D.S. prior to use
Provide adequate ventilation
Prolonged skin contact
Inhalation of vapour must be avoided
Eye contamination - Flush with eyewash or warm water for 10 minutes.
Clean hands after use.

Any person or company using this product without first making enquiries as to the suitability for the intended purpose does so at their own risk, and Premier Marine Paints Ltd can accept no liability for.

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Tel: 01884 220016
Email: Sales@premiermarinepaints.com
www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942

