TECHNICAL DATA SHEET

PREMIER CLASSIC YACHT VARNISH ref 53L644

A quality traditional high gloss finish. flexible with excellent UV and scratch resistance. Good flow for easy application. Suitable for interior & exterior in most industrial/commercial and marine environments, where 2 coats give optimum performance.



Surface Preparation

Ensure surface is free from rust, moisture, oil or other surface contamination.

When applying over previously varnished wood, ensure the surface is clean and sand smooth. After sanding, ensure all sanding dust is removed and wipe down with thinners. If the previously varnished wood is in poor condition then we recommend removing all previous coats.

When applying to bare wood, sand smooth and remove any dust and wipe down with thinners. The first coat may be thinned by 10% using Thinners No. 2.

Application

Brush or Roll and for best results lightly sand between coats using a fine 320 – 400 grade/grit paper.

Do not apply in temperatures below 5°c and ensure that the substrate temperature is above 5°c

Avoid applying late in the day as temperatures drop, to allow the varnish to dry without the risk of condensation forming. Condensation will result in a loss of gloss finish.

PACKAGE SIZE 1 Litre

COLOUR Clear

FLASH POINT Above 32°C

DRYING TIME @ 20°C Surface Dry: 4 - 6 hrs

VOLUME SOLIDS 48% (+/- 2%)

RECOMMENDED W.F.T. 120 microns

RECOMMENDED D.F.T. 58 microns

THEORETICAL SPREADING RATE 8 Sq. Metres/Litre

THINNERS No. 2

SHELF LIFE 12 months

V.O.C. 395 g/litre

Health & Safety

Refer to M.S.D.S. prior to use Provide adequate ventilation Prolonged skin contact Inhalation of vapour must be avoided Eye contamination - Flush with eyewash or warm water for 10 minutes Clean hands after use

Any person or company using this product without first making enquiries as to the suitability for the

intended purpose does so at their own risk, and Premier Marine Paints Ltd can accept no liability for

Tel: 01884 220016

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

