## PREMIER CLASSIC YACHT VARNISH

Ref: 53L644

DATE: 06/04/11 REPLACES: BY:

1. <u>IDENTIFICATION OF THE PREPARATION:</u>

PRODUCT: PREMIER CLASSIC YACHT VARNISH REF: 53L644

2. <u>COMPOSITION/INFORMATION ON INGREDIENTS:</u>

**INGREDIENTS:** Aliphatic Hydrocarbons R10, 52, 53 Xn 28 – 33%

3. HAZARDS IDENTIFICATION:

Harmful by inhalation and in contact with skin, irritating to eyes and respiratory system, flammable.

4. FIRST AID MEASURES:

**INHALATION:** Remove to fresh air, if conscious turn into recovery position. Get medical help.

**SKIN:** Wash with soap and water.

**EYES:** Flush out with clean water for 10 minutes. Get medical help.

**INGESTION:** Seek urgent medical attention.

5. FIRE FIGHTING MEASURES:

**SMALL FIRES:** Use Carbon Dioxide, dry chemical, foam, sand, earth or water fog. **LARGE FIRES:** Use foam or water fog. Keep containers cool by spraying with water.

N.B.

Decomposition products will give rise to toxic fumes. Self-contained breathing apparatus must be worn.

6. <u>ACCIDENTAL RELEASE MEASURES:</u>

In case of spillage, extinguish all ignition sources; avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage using vermiculite, dry sand or earth and place in container. Avoid inhaling vapour, evacuate personnel from the area. If it has entered the drains, inform the appropriate authorities (fire service).

#### 7. HANDLING & STORAGE:

Avoid contact with skin or eyes. Avoid breathing vapours. Handle in a well-ventilated workspace. Empty containers may contain explosive vapours. Flush empty containers with water to remove residual flammable liquid and vapours. Smoking in area is prohibited. Remove all equipment, which may be sources of ignition, from vicinity while handling.

Tel: 01884 220016

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No.:139600418 Company Registration No.: 8002942



## PREMIER CLASSIC YACHT VARNISH

Ref: 53L644

#### 8. **EXPOSURE CONTROL/PERSONAL PROTECTION:**

INGREDIENT CAS no STD LONGTERM EXPOSURE (8HF SHORT TERM EXPOSUF

Aliphatic

Hydrocarbons 64742-82-1 OEL 100 ppm 125 ppm

**EYE PROTECTION:** Close fitting goggles or face shield **SKIN PROTECTION:** Overalls with solvent resistant gloves

**RESPIRATORY PROTECTION:** In poorly ventilated areas a cartridge mask suitable for

solvent vapours and toxic particles is recommended.

#### 9. PHYSICAL & CHEMICAL PROPERTIES

COLOUR: Various GLOSS: Full

VISCOSITY: 6-8 POISE R/T @ 20°C

**DRYING:** Touch Dry: 4 - 6 hrs Hard Dry:

CURE: N/A

APPLICATION VISC: As supplied

THINNERS: 50/2 MIXING RATIO: N/A

**SUPPLIED SOLIDS:** Volume: 48 +/- 2% Weight:

10sqmtr/ltr

CALCULATED SUPPLIED V.O.C: 395 g/Ltr +/- 20 g/Ltr

COVERAGE: FLASH POINT: Above 32°C RESISTANCE:

N/A S.G:

#### 10. STABILITY & REACTIVITY:

**STABILITY:** 

Stable

**REACTION WITH WATER:** 

None

**DANGEROUS REACTIONS:** 

None known

**HAZARDOUS POLYMERISATION:** 

Will not occur

**MATERIALS TO AVOID:** 

Strong oxidising agents

Tel: 01884 220016

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No:139600418 Company Registration No: 8002942



## PREMIER CLASSIC YACHT VARNISH

Ref: 53L644

#### **DANGEROUS DECOMPOSITION PRODUCTS:**

Carbon Monoxide, Carbon dioxide and Nitrogen Dioxide. Nitrogen Dioxide reacts with water to form corrosive Nitric Acid.

#### 11. TOXICOLOGICAL INFORMATION:

Can cause irritation to eyes, mucous membranes and skin.

#### 12. <u>ECOLOGICAL INFORMATION:</u>

Harmful to the aquatic environment, may cause long-term adverse effects to the aquatic environment.

#### 13. <u>DISPOSAL CONSIDERATIONS:</u>

This material must be disposed of via an Authorised Waste Disposal Company in accordance with Local and National Waste Disposal Regulations.

#### 14. TRANSPORT INFORMATION:

HAZARD CLASS:

UN NUMBER:

HAZARD LABEL:

PACKING GROUP:

TREMCARD NO:

MARINE POLLUTANT:

3

1263

Flammable Liquid Paint Class 3

Flammable Liquid Paint Class 3

Yes

A.D.R:

Class 3 item 3,1 (c)

#### 15. **REGULATORY INFORMATION:**

PRIMARY RISK: Flammable SECONDARY RISK: Harmful

**LABEL RISK PHRASES:** 

R10 Flammable

R20 Harmful by inhalation

R21 Harmful by contact with skin

R22 Harmful if swallowed

R23 Toxic by inhalation

R38 Irritating to skin

R52 Harmful to aquatic environment

Tel: 01884 220016

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No:139600418 Company Registration No: 8002942



## PREMIER CLASSIC YACHT VARNISH

Ref: 53L644

R53 May cause long-term adverse effects in the aquatic environment

#### **LABEL SAFETY PHRASES:**

S9	Keep containers in a well-ventilated place
S16	Keep away from sources of ignition
S23	Do not breathe vapour
S29	Do not empty into drains
S33	Take precautionary measures against static discharge

\$38 In case of insufficient ventilation wear suitable respiratory equipment

#### 16. <u>OTHER INFORMATION:</u>

For further Health and Safety information contact the above address.

The information given in this leaflet has been complied on the basis of best availability knowledge. It does not imply that the information is complete or accurate in all cases. It is the user's responsibility to satisfy him/herself as to the implication of the information and/or the recommendations given for his/her own use.

Tel: 01884 220016

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No:139600418 Company Registration No: 8002942

