MATERIAL SAFETY DATA SHEET

PREMIER HULL & TOPSIDE PAINT

Ref: 53L642

DATE: 06/04/11 REPLACES: BY:

1. <u>IDENTIFICATION OF THE PREPARATION:</u>

PRODUCT: PREMIER HULL & TOPSIDE YACHT PAINT **REF:** 53L642

2. COMPOSITION/INFORMATION ON INGREDIENTS:

INGREDIENTS: Aliphatic Hydrocarbons R10, 52, 53 25 – 35%

3. HAZARDS IDENTIFICATION:

Harmful by inhalation and in contact with skin, irritating to eyes and respiratory system, flammable.

4. FIRST AID MEASURES:

INHALATION: Remove to fresh air, if conscious turn into recovery position. Get medical help.

SKIN: Wash with soap and water.

EYES: Flush out with clean water for 10 minutes. Get medical help.

INGESTION: Seek urgent medical attention.

5. FIRE FIGHTING MEASURES:

SMALL FIRES: Use Carbon Dioxide, dry chemical, foam, sand, earth or water fog. **LARGE FIRES:** Use foam or water fog. Keep containers cool by spraying with water.

N.B.

Decomposition products will give rise to toxic fumes. Self-contained breathing apparatus must be worn.

6. ACCIDENTAL RELEASE MEASURES:

In case of spillage, extinguish all ignition sources; avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage using vermiculite, dry san earth and place in container. Avoid inhaling vapour, evacuate personnel from the area. If it has entered the drains, inform the appropriate authorities (fire service).

7. HANDLING & STORAGE:

Avoid contact with skin or eyes. Avoid breathing vapo Handle in a well-ventilated workspace. Empty containers may contain explosive vapours. Flush empty containers with water to remove residual flammable liquid and vapours. Smoking in area is prohibited. Remove all equipment, which may be sources of ignition, from vicinity while handling.

8. EXPOSURE CONTROL/PERSONAL PROTECTION:

INGREDIENT CAS no STD LONGTERM EXPOSURE (8HRSH) ORT TERM EXPOSURE Aliphatic

Hydrocarbons 64742-82-1 OEL 100 ppm 125 ppm

EYE PROTECTION: Close fitting goggles or face shield

Tel: 01884 220016

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No:139600418 Company Registration No: 8002942



MATERIAL SAFETY DATA SHEET

PREMIER HULL & TOPSIDE PAINT

Ref: 53L642

SKIN PROTECTION: Overalls with solvent resistant gloves

RESPIRATORY PROTECTION: In poorly ventilated areas a cartridge mask suitable f r solvent vapours

and toxic particles is recommended.

9. PHYSICAL & CHEMICAL PROPERTIES

COLOUR: Various GLOSS: Full

VISCOSITY: 6 – 8 poise R/T @ 20°C

DRYING: Touch Dry: 4 – 6 hrs Hard Dry: O/N

CURE: N/A

APPLICATION VISC: As supplied

THINNERS: 50/2 MIXING RATIO: N/A

SUPPLIED SOLIDS: 45 +/- 5%by weight 37 +/- 5%by Volume

CALCULATED SUPPLIED V.O.C: 500gms/Ltr

COVERAGE: 13 – 15sqm/Ltr @25microns DFT

FLASH POINT: 22 – 55°C

RESISTANCE: N/A

S.G: 1.09 +/- 0.03

10. STABILITY & REACTIVITY:

STABILITY: Stable
REACTION WITHWATER: None
DANGEROUS REACTIONS: None known
HAZARDOUS POLYMERISATION: Will not occur

MATERIALS TO AVOID: Strong oxidising agents

DANGEROUS DECOMPOSITION PRODUCTS: CarbonMonoxide, Carbon dioxide and Nitrogen

Dioxide. Nitrogen Dioxide reacts with water to form

corrosive Nitric Acid.

11. TOXICOLOGICAL INFORMATION:

Can cause irritation to eyes, mucous membranes and skin.

12. **ECOLOGICAL INFORMATION:**

Harmful to the aquatic environment, may cause long-term adverse effects to the aquatic environment.

13. <u>DISPOSAL CONSIDERATIONS:</u>

This material must be disposed of via an Authorised Waste Disposal Company in accordance with Local and National Waste Disposal Regulations.

Tel: 01884 220016

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No:139600418 Company Registration No: 8002942



MATERIAL SAFETY DATA SHEET

PREMIER HULL & TOPSIDE PAINT

Ref: 53L642

14. TRANSPORT INFORMATION:

HAZARD CLASS: 3 UN NUMBER: 1263

HAZARD LABEL: Flammable Liquid Paint Class 3

PACKING GROUP: 3
TREMCARD NO: 33
MARINE POLLUTANT: Yes

A.D.R: Class 3 item 3,1 (c)

15. **REGULATORY INFORMATION:**

PRIMARY RISK: Flammable SECONDRY RISK: Harmful

LABEL RISK PHRASES: R10 Flammable

R20 Harmful by inhalation
R21 Harmful by contact with skin
R22 Harmful if swallowed
R23 Toxic by inhalation
R38 Irritating to skin

R52 Harmful to aquatic environment

R53 May cause long-term adverse effects in the aquatic environment

LABEL SAFETY PHRASES: S9 Keep containers in a well-ventilated place

\$16 Keep away from sources of ignition

S23 Do not breathe vapourS29 Do not empty into drains

S33 Take precautionary measures against static dischargeS38 In case of insufficient ventilation wear suitable respiratory

16. OTHER INFORMATION:

For further Health and Safety information contact the above address.

The information given in this leaflet has been complied on the basis of best availability knowledge. It does not imply that the information is complete or accurate in all cases. It is the user's responsibility to satisfy him/herself as to the implication of the information and/or the recommendations given for his/her own use.

Tel: 01884 220016

Email: Sales@premiermarinepaints.com

www.premiermarinepaints.com

VAT No:139600418 Company Registration No: 8002942

