

TECHNICAL DATA SHEET

PREMIER CRUISING PLUS ANTIFOUL

Ref: 80L626

An all purpose self eroding antifouling in a range of colours for all cruising yachts. High strength copper based.



Substrates:

Boat Hulls GRP, wood, steel and ferro cement.
Not suitable for aluminium or galvanised surfaces.

Packaging Size: 2.5 litres
Colour: Black, Dark Blue, Light Blue, Red and Steel White
Finish: Matt
Theoretical spreading rate: 10 sq. metres per litre
Flash point: Less than 32°C

DRYING TIMES (in hours)

Outside Temp	Touch Dry	Overcoat Time
5°C	1.5 Hours	3.0 Hours
10°C	1.5 Hours	3.0 Hours
15°C	1.0 Hours	2.5 Hours
20°C	1.0 Hours	2.0 Hours
25°C	0.5 Hours	2.0 Hours

DO NOT APPLY AT TEMPERATURES OF LESS THAN 5°C

Craft should be launched within 2–3 months after application, dependent on ambient temperature.

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application:

Application method: Apply by brush, roller or pad.

Thinner: Premier Antifouling Thinners Base 1 or any antifouling thinners base 1. Maybe thinned up to maximum 10%

Cleaning of tools: Premier Antifouling Thinners

Surface condition:

Ensure surface is free from rust, moisture, oil or other surface contamination. Previously painted surfaces should be well abraded to ensure good key for the following coating.

Please refer to the Material Safety Data Sheet for further information. For additional guidance please contact your local Technical Sales Representative.

Premier Marine Paints Ltd
The Engine Shed
Lenham Heath Road
Lenham Heath
Maidstone
Kent
ME17 2BS

Tel: 01884 220016
Email: Sales@premiermarinepaints.com
www.premiermarinepaints.com

VAT No: 139600418
Company Registration No: 8002942

